

## Style 005

### End Cap

Publication: 01.09.04EN




Nominal Size	OD	EE	Approx. Wt. Ea.
Inches mm	Inches mm	Inches mm	Lbs. kg
1¼	1.660	0.91	0.2
32	42.4	23	0.1
1½	1.900	0.91	0.4
40	48.3	23	0.2
2	2.375	0.98	0.4
50	60.3	25	0.2
2½	2.875	0.98	0.7
65	73.0	25	0.3
3OD	3.000	0.98	0.7
65	76.1	25	0.3
3	3.500	0.98	0.9
80	88.9	25	0.4
4	4.500	0.98	1.1
100	114.3	25	0.5
5½OD	5.500	0.98	2.2
125	139.7	25	1.0
5	5.563	0.98	2.2
125	141.3	25	1.0
6½OD	6.500	0.98	3.1
150	165.1	25	1.4
6	6.625	0.98	3.1
150	168.3	25	1.4
8	8.515	1.22	8.4
200A %	216.3	31	3.8
8	8.625	1.22	8.4
200	219.1	31	3.8
10	10.525	1.22	13.9
250A %	267.4	31	6.3
10	10.750	1.22	14.1
250	273.0	31	6.4
12	12.539	1.22	19.6
300A %	318.5	31	8.9
12	12.750	1.22	19.8
300	323.9	31	9.0

## Style 005WH

### End Cap with Hole

Publication: 01.09.11EN



Nominal Size	OD	T	t	h	Approx. Wt. Ea.
Inches mm	Inches mm	Inches mm	Inches mm	Inches mm	Lbs. kg
2	2.375	1.10	0.98	0.28	0.7
50	60.3	28	25	7.0	0.3
2½	2.875	1.10	0.98	0.51	0.9
65	73.0	28	25	13.0	0.4
3OD	3.000	1.10	0.98	0.55	0.9
65	76.1	28	25	14.0	0.4
3	3.500	1.10	0.98	0.81	1.1
80	88.9	28	25	20.5	0.5
4	4.500	1.10	0.98	1.38	1.5
100	114.3	28	25	35.0	0.7
5½OD	5.500	1.10	0.98	1.79	2.0
125	139.7	28	25	45.4	0.9
5	5.563	1.10	0.98	1.79	2.0
125	141.3	28	25	45.4	0.9
6½OD	6.500	1.10	0.98	2.26	3.3
150	165.1	28	25	57.5	1.5
6	6.625	1.10	0.98	2.32	3.3
150	168.3	28	25	59.0	1.5
8	8.625	1.73	1.22	3.15	9.3
200	219.1	44	31	80.0	4.2
10	10.750	1.73 #	1.22	4.27	32.6
250	273.0	44 #	31	108.5	14.8
12	12.750	1.73 #	1.22	5.19	46.3
300	323.9	44 #	31	132.0	21.0

- UL Listed and FM Approved pressure rate of Style 005 and 005WH End Cap is the same as Style 001 coupling, for details please refer to page15.
- Style 005 End Cap is not suitable for use in vacuum service unless with extra treatment. For example, Inlet of fire pump, Style 005B is recommended to use.
- Style 005WH is not suitable for use in vacuum service unless with extra treatment. For example, Inlet of fire pump, Style 005B is recommended to use, Style 005B refer to "General Catalog".
- Hole size of Style 005WH can be customized.
- For correct installation, please refer to page 91 "General of Installation" and Publication AZ-100-EN "Installation Manual".
- For ONE TIME FIELD TEST ONLY, the Max. Joint working pressure may be increased to 1.5 times the figures shown.

LPC refer to page 13 for details.  
% JIS Standard  
# Segmentally Welded Steel.

